
AP03

防味防塵空氣淨化機

AP03 Odour & Dust Control Air Purifier



燈具細節



定時殺菌燈

半透明玻璃保護層

顆粒物 CADR

1,200 m^3/h

建議適用面積

30–150 m^2

濾芯展開面積

20 m^2

AP03 配備多重過濾，協助去除 PM2.5、霧霾、灰塵、粉塵及花粉，
並兼顧二手煙、油煙、甲醛及異味處理，配合定時殺菌燈進行室內空氣淨化。

產品賣點
Product Features

- **過濾 PM2.5 及粉塵**
  協助減少 PM2.5、霧霾、灰塵、粉塵及花粉等空氣中的顆粒物。
- **煙霧及異味處理**
  針對二手煙、油煙及日常異味，配合多重過濾設計進行淨化。
- **兼顧甲醛淨化**
  甲醛 CADR 為 175.3 m^3/h，甲醛 CCM 等級為 F4。
- **大濾芯配合大風量**
  20 m^2 濾芯展開面積、高容塵量，出風量 1,000–1,700 m^3/h。
- **定時殺菌燈設計**
  設半透明玻璃保護層，燈具支援定時運作。
- **腳輪設計，方便移位**
  機底附腳輪，方便調整擺放位置，配合日常室內使用。

技術規格
Technical Specifications

型號	AP03
顆粒物 CADR	1,200 m^3/h
甲醛 CADR	175.3 m^3/h
顆粒物 CCM 等級	P4
甲醛 CCM 等級	F4
出風量	1,000–1,700 m^3/h
建議適用面積*	30–150 m^2
噪音	28–38 dB
過濾設計	多重過濾
濾芯展開面積	20 m^2
殺菌燈	支援定時
移動方式	底部腳輪
機器重量	約 40 kg
尺寸（高×闊×深）	1,240 × 575 × 370 mm

* 規格按供應商資料整理。建議適用面積及實際淨化效果視現場環境與使用條件而定。
產品圖片為外觀參考；尺寸順序為高 × 闊 × 深。


香港新界葵涌大連排道182–190號金龍工業中心4座4樓D&E室
hkmisting.com | admin@hkmisting.com
WhatsApp / Tel +852 5503 8458

AP03

Odour & Dust Control Air Purifier



Lamp detail



Timed germicidal lamp
Translucent glass protective layer

Particle CADR
1,200 m³/h

Recommended room area
30–150 m²

Unfolded filter area
20 m²

AP03 uses multi-layer filtration to help reduce PM2.5, haze, dust, fine dust and pollen.

It also helps manage second-hand smoke, oil fumes, formaldehyde and odours, with a timed germicidal lamp.

Product Features

- **PM2.5 and dust filtration**
  Helps reduce PM2.5, haze, dust, fine dust and pollen suspended in the air.
- **Smoke and odour control**
  Multi-layer filtration helps manage second-hand smoke, oil fumes and odours.
- **Formaldehyde reduction**
  Formaldehyde CADR: 175.3 m³/h.
  Formaldehyde CCM grade: F4.
- **Large filter and high airflow**
  20 m² unfolded filter area; high dust capacity.
  Airflow: 1,000–1,700 m³/h.
- **Germicidal lamp with timer**
  Translucent glass protective layer.
  Timer-controlled lamp operation.
- **Castors for easy repositioning**
  Base-mounted castors make it easier to reposition the unit for everyday indoor use.

Technical Specifications

Model	AP03
Particle CADR	1,200 m³/h
Formaldehyde CADR	175.3 m³/h
Particle CCM grade	P4
Formaldehyde CCM grade	F4
Airflow	1,000–1,700 m³/h
Recommended area*	30–150 m²
Noise level	28–38 dB
Filtration	Multi-layer filtration
Unfolded filter area	20 m²
Germicidal lamp	Timer function
Mobility	Base-mounted castors
Machine weight	Approx. 40 kg
Dimensions (H × W × D)	1,240 × 575 × 370 mm

* Specifications are based on supplier information. Recommended area and purification performance depend on site conditions and use.
Product image is for appearance reference. Dimensions are shown as height × width × depth.

Units D & E, 4/F, Block 4, Golden Dragon Industrial Centre,
182–190 Tai Lin Pai Road, Kwai Chung, N.T., Hong Kong
hkmisting.com | admin@hkmisting.com
WhatsApp / Tel +852 5503 8458