



香港霧業 Hong Kong Misting
全面環境治理．重塑空間價值

索取報價

WhatsApp / Tel +852-5503-8458



C09 – 戶外防水掛牆式噴霧風扇

高效降溫・舒適戶外空間的智慧選擇



設計之選

時尚現代設計，完美融入各種戶外環境。



自動補水

內置自動進水系統，無需外接大水箱，使用更方便。



長效噴霧

優化噴霧系統，帶來持久清涼體驗。



可調節霧量

根據需求調整噴霧強度，靈活舒適。



高效送風

風距可達 10 米，有效覆蓋更大範圍。



CE IPX5

技術規格

尺寸 (長 x 高 x 深)	47 x 116 x 63 cm
電源需求	220V, 60Hz, 320W
風速 (約)	~1700 rpm
風量	2,450 m ³ /hr
耗水量	6-10 L/hr

風距	最遠可達 10 米
擺頭角度	90° 擺頭
噴霧持續時間	由水陷自動補水
防水等級	IPX5
噪音水平	< 67 dB



節能省水



易於安裝



耐用抗 UV 材質



防鏽防腐蝕設計

產品資訊由廠方提供，僅供參考，規格可能隨時更新且恕不另行通知



香港霧業 Hong Kong Misting
全面環境治理．重塑空間價值

索取報價

WhatsApp / Tel +852-5503-8458



C09 Outdoor Centrifugal Wall-mount Misting Fan

Efficient Cooling for Comfortable Outdoor Spaces

A smart cooling choice for outdoor commercial environments



Designer Choice

Modern, stylish appearance that blends naturally into a wide range of outdoor spaces.



Auto Fill Water

Built-in automatic water refill system for greater convenience.



Long Misting Hours

Optimized misting system for long-lasting cooling comfort.



Adjustable Mist Volume

Mist output can be adjusted to suit different site needs.



Wind Distance Up to 10 m

Strong airflow delivers cooling mist across a wider area.



IPX5

TECHNICAL SPECIFICATIONS

	Dimensions (L x H x D):	47 x 116 x 63 cm
	Power Requirement:	220V, 60Hz, 320W
	Fan Speed (Approx.):	~1700 rpm
	Airflow:	2,450 m ³ /hr
	Water Consumption:	6-10 L/hr

	Wind Distance:	Up to 10 m
	Swing Angle:	90° oscillation
	Mist Duration:	Auto-refilled by water line
	Protection Rating:	IPX5
	Noise Level:	< 67 dB

APPLICATIONS



Restaurant / Terrace



Mall Entrance



Outdoor Leisure Area



Outdoor Commercial Space



Water-Saving



Easy Installation



Durable
UV-Resistant Materials



Moisture & Corrosion
Resistant Design

Product information is provided by the manufacturer for reference only. Specifications are subject to change without prior notice.