



DE-01

工業住家兩用抽濕機(水管/水箱兩用)

Industrial and residential dehumidifier (water tank)




Power supply	220-240V/50HZ
Control	TOUCH PANEL
Moisture removal	40L/Day
Power consumption 30°C,RH80%	580W
Operating current 30°C,RH80%	3.9A
Refrigerant type	R410A
Design pressure	6.5MPa
Air Flow	230m ³ /h
Noise level	52dB(A)
Dimension (W*D*H)	315mm*230mm*590mm
Net/Gross weight	16.5kg / 17.6kg
Stuffing quantity (20'FT/40'GP/40'HQ)	51/738/984
Ambient temp	5°C - 32°C
Range of rel.humidity	50% - 80%

Specification

- Compact and elegant design
- Water full auto stop
- Easy handle
- Injection housing
- Auto defrost
- Adjustable fan speed(Hi / Lo)
- Electronic control panel
- Clever timer
- Humidity setting: R.H. 30%, 35%, 40%.....90%,
comfort mode & Continuous dehumidifying



Features

-  Water full auto stop
-  Easy setup, plug and play
-  Steady wheels

Call Now
5503 8458

www.hkmisting.com

一機工商住宅兩用



自由·不受限制 滿足各個區域除濕要求





DE-01

工業住家兩用抽濕機(水管/水箱兩用)

Industrial and residential dehumidifier (water tank)




Power supply	220-240V/50HZ
Control	Electronic
Moisture removal	70L/Day
Power consumption 30°C,RH80%	830W
Operating current 30°C,RH80%	3.9A
Refrigerant type	R410A
Design pressure	2.5MPa
Water tank volume	4.5L
Noise level	54dB(A)
Dimension (W*D*H)	405mm*632mm*268mm
Net/Gross weight	18.8kg / 19.8kg
Stuffing quantity (20'FT/40'GP/40'HQ)	279/558/741
Ambient temp	5°C - 32°C
Range of rel.humidity	30% - 80%



Specification

- Easy handle
- Adjustable fan speed
- Electronic control panel
- Clever timer
- Injection housing
- Humidity setting: R.H. 30%,40%, 50%, 60%, 70%, 80%, comfort mode & Continuous dehumidifying

Features

-  Water full auto stop
-  Easy setup, plug and play
-  Steady wheels

Call Now
5503 8458

www.hkmisting.com

一機工商住宅兩用



自由·不受限制 滿足各個區域除濕要求

