



DE-04(A~F)

大功率工業用抽濕機(排水管型)

Power consumption	220V~380V/ 2.8kw~7.2kw
Dehumidification	168L~480L/Day (30℃ 80%RH)
Serving area	200~600m ²
Water Tank	water pipe only
Weight	112~240kg



1. External drainage pipe
2. LED control panel
3. Humidity sensor for detecting and measuring water vapor
4. Timer setting: range from 1 to 24hours
5. RH humidity setting 10% ~90%
6. UVC Germicidal
7. With 4 casters at the bottom
8. Build-in dust filter
9. Fault diagnosis

Call Now

5503 8458

www.hkmisting.com

詳細數據

型 號	DE04A	DE04B	DE04C	DE04D
電 壓	220V/50HZ	380V/50HZ	380V/50HZ	380V/50HZ
除 濕 量	168L/D	210L/D	240L/D	360L/D
最大功率	2.8kW	4.12KW	4.9kW	7.2KW
電 流	12.8A	6.3A	7.4A	11A
處理風量	1520m3/h	2300m3/h	2600m3/h	4000m3/h
過濾裝置	初效	初效	初效	初效
濕度可調範圍	10-90%	10-90%	10-90%	10-90%
控制方式	自動除濕	自動除濕	自動除濕	自動除濕
壓縮機品牌	日立	日立	日立	日立
排水方式	軟管直排	軟管直排	軟管直排	軟管直排
水管直徑	16mm	16mm	16mm	16mm
適用面積	200-300㎡	250-350㎡	300-400㎡	500-600㎡
機身尺寸	寬610*深400*高1600mm	寬770*深470*高1750mm	寬770*深470*高1750mm	寬1190*深450*高1750mm
雪 種	R410A	R410A	R410A	R410A
重量	112KG	155KG	158KG	240KG



高品質的金屬用料

1 2 3

高硬度材料

韌性好, 硬度高

高耐磨材料

抗低溫衝擊性能,
耐磨

抗氧化腐蝕

表面均噴有抗氧
化, 抗腐蝕特性



360度
高強度萬向輪

外接式排水水管

外接式排水水管, 直接排入下水管道, 免除工業除濕頻繁更換水箱的煩惱



高密度過濾網

有效過濾空氣中的顆粒與塵埃, 降低對電路的損害, 延長機器壽命

